

**M-800-L4  
ENDWHEEL  
25MM**

# WHEEL STEERING TRUCK

## Pneumatic wheel with steel rim, axle Ø25mm.

Pneumatic wheel with steel rim, axle Ø25mm.

- Pneumatic 4ply tyre.
- 'PLY' rating is used to state how many plies (layers) of rubber were woven into the construction of the tyre. This rating indicates the strength and carrying capacity of the tyre.
- Steel rim with double closed ball bearings.
- Ø25mm axle.
- Very strong and stays on course.
- Capacity: 250 Kg.
- Rim is completely powder-coated in red. Resistant powder coating. (no solvents, less harmful to the environment).



10620  
M-800-L4 ENDW. 25MM

- Pneumatic 4ply tyre.
- Steel rim with double closed ball bearings.
- Axle Ø25mm.
- Rim is completely powder-coated in red.
- Very strong and stays on course.



Cap. (kg)	Dimensions ØxW (mm)	Weight (kg)	Axle Ø (mm)	Tyre	Material tyre	Material rim	Article	Art. nr
250	400-8/16x4" 400x100	2,8	25	Pneumatic	4ply rubber	Steel, red powdercoated	M-800-L4 ENDW. 25MM	10620
							Starlockborger, spring steel	10113