

M-800-L4-15

WHEELBARROW WHEEL

wheelbarrow wheel Pneumatic tyre and with steel rim

M-800-L4 pneumatic wheelbarrow wheel with steel rim.

- Pneumatic 4ply tyre.
- 'PLY' rating is used to state how many plies (layers) of rubber were woven into the construction of the tyre. This rating indicates the strength and carrying capacity of the tyre.
- Steel rim with double closed ball bearings.
- Ø20mm axle.
- Axle length 150mm. (standard length)
- Very strong and stays on course.
- Capacity: 250 Kg.
- Rim is completely powder-coated in gray. Resistant powder coating. (no solvents, less harmful to the environment).



- Pneumatic 4ply tyre
- Steel rim with double closed ball bearings.
- Axle Ø20mm.
- Axle length 150mm. (standard length)
- Rim is completely powder-coated in gray
- Very strong and stays on course.



11170
M-800-L4-15

| Cap. (kg) | Dimensions ØxW (mm) | Weight (kg) | Axle length (mm) | Axle Ø (mm) | Tyre | Material tyre | Material rim | Article | Art. nr |
|--------------|---------------------------|----------------|------------------------|----------------|-----------|---------------|-----------------------------|-------------|---------|
| 250 | 400-8/16x4" 400x100 | 3 | 150 | 20 | Pneumatic | 4ply rubber | Steel, gray powdercoated | M-800-L4-15 | 11170 |