

**M-800-L4-
ENDWHEEL**

WHEELBARROW WHEEL

wheelbarrow wheel Pneumatic tire and with steel rim

M-800-L4 pneumatic wheelbarrow wheel with steel rim.

- Pneumatic 4ply tire.
- 'PLY' rating is used to state how many plies (layers) of rubber were woven into the construction of the tire. This rating indicates the strength and carrying capacity of the tire.
- Steel rim with double closed ball bearings.
- Axle hole Ø20mm.
- Very strong and stays on course.
- Capacity: 250 Kg.
- Rim is completely powder-coated in gray. Resistant powder coating. (no solvents, less harmful to the environment).



13528
M-800-2WIL4-ENDWHEEL

- Pneumatic 4ply tire
- Steel rim with double closed ball bearings.
- Axle hole Ø20mm.
- Rim is completely powder-coated in gray
- Very strong and stays on course.



Cap. (kg)	Dimensions ØxW (mm)	Weight (kg)	Axle hole Ø (mm)	Tire	Material tire	Material rim	Article	Art. nr
250	400-8/16x4" 400x100	3	20	Pneumatic	4ply rubber	Steel, gray powdercoated	M-800-2WIL4-ENDWHEEL	13528
	Inner: 20 Outer: 36	0,01	20				M-981.20 starlock fastborger (to securing tyre)	11220