

**M-800-L4-
BLOCK**

WHEELBARROW WHEEL

wheelbarrow wheel pneumatic tyre and with steel rim

M-800-L4 pneumatic wheelbarrow wheel with block profile and steel rim.

- Pneumatic 4ply tyre.
- 'PLY' rating is used to state how many plies (layers) of rubber were woven into the construction of the tyre. This rating indicates the strength and carrying capacity of the tyre.
- Steel rim with double closed ball bearings.
- Ø20mm axle.
- Axle length 150mm. (standard length)
- Very strong and stays on course.
- Capacity: 250 Kg.
- Rim is completely powder-coated in gray. Resistant powder coating. (no solvents, less harmful to the environment).



15082
M-800-L4-BLOCK

- Pneumatic 4ply tyre with block profile.
- Steel rim with double closed ball bearings.
- Axle Ø20mm.
- Axle length 150mm. (standard length)
- Rim is completely powder-coated in gray
- Very strong and stays on course.



Cap. (kg)	Dimensions ØxW (mm)	Weight (kg)	Axle length (mm)	Axle Ø (mm)	Tyre	Material tyre	Material rim	Article	Art. nr
250	400-8/16x4" 400x100	3	150	20	Pneumatic	4ply rubber block profile	Steel, gray powdercoated	M-800-L4-BLOCK	15082