

**M-NOKA
230-CT
ELECTRIC**

WHEELBARROWS

NOKA-230 ELECTRIC

NOKA-230-CT-ELECTRIC AGRI WHEELBARROW WITH XTRA WIDE PNEUMATIC TIRES

M-NOKA 230-CT-ELECTRIC is an electric driven agricultural wheelbarrow with 2 Xtra wide puncture proof tires.

Easy to operate by the 2 sliding handles. The more resistance when pushing the wheelbarrow the more the engine takes over.

Extra wide puncture proof tyre Ø400x130mm. Equipped with special integrated motor with a capacity more than 600 Watt. Max 6 Km/h.

Strong 6 mm HDPE tray(230 liters) with extra reinforcement around the nose of the tray.

Oval tube, (lighter and stronger) for heavy use.

Wear pads for a longer service life of the legs.

Easy to tilt thanks to the rounded shape of the chassis.

Natural rubber ergonomic hand-shaped handles with knuckle protection.

Frame is completely powder-coated in gray. Resistant powder coating. (no solvents, less harmful to the environment).

Xtra wide puncture proof PU-tires (foamed Polyurethan).



18758
M-NOKA 230-CT-
ELECTRIC



- Reduces the physical load
- Over steep slope, e.g. when unloading in a container, goes smoothly.
- Uphill driving is very comfortable.
- Battery charges when driving downhill.
- Easy to ride through soft soil.
- Direct drive
- Alternating Current (AC)
- Gearless (less parts, more durable)
- Low noise.
- Top energy efficient.
- Li-ion battery with sophisticated battery management.
- Normal working with wheelbarrow for 8 hours on single battery charge (Depending on the user and application).
- Charging time 3 hours.
- Lifespan (from 0% to 100% State Of Charge): 500 cycles to 70%.
- Lifespan (from 30 to 70% State Of Charge): up to 10000 cycles to 70% capacity.
- You can move forward and backward without pushing your hand (Push-Pull).



Dual drive through
the handles



Cap. (kg)	Dim.overall LxWxH (mm)	Dim. tray LxWxH (mm)	Weight (kg)	Torque	Battery	charge temp.	Dis-charge temp.	Input / output voltage	Protection rating	Article	Article-nr
250	1600x900x730	1100x880x380/590	26	25Nm	36V, 10,5 Ah, Lithium	4-40°C	-20-60°C	200/240V AC 42V / 5A	IP65	M-NOKA 230-CT- ELECTRIC	18758
	130x55x38		0,12							M-970-Z RUB	12337
		1100x880x380/590								M-BAK GREEN 230L	16055
	175x92x50		0,812			4-40°C		200/240V AC 42V / 5A		M-E-BARROW CHARGER	18227